

Mini Spot

Fixed trimless Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 35 mm
-  White (WH)
-  Black (BK)
-  Chrome (CH)



DIM



TUNABLE WHITE



Wattage	Beam Angle	2700K	3000K	4000K	2700~6500K
Max. 5W	 15°	10.3510.WH	10.3511.WH	10.3512.WH	10.3522.WH
		10.3510.BK	10.3511.BK	10.3512.BK	10.3522.BK
		10.3510.CH	10.3511.CH	10.3512.CH	10.3522.CH
	 24°	10.3513.WH	10.3514.WH	10.3515.WH	10.3523.WH
		10.3513.BK	10.3514.BK	10.3515.BK	10.3523.BK
		10.3513.CH	10.3514.CH	10.3515.CH	10.3523.CH
	 36°	10.3516.WH	10.3517.WH	10.3518.WH	10.3524.WH
		10.3516.BK	10.3517.BK	10.3518.BK	10.3524.BK
		10.3516.CH	10.3517.CH	10.3518.CH	10.3524.CH

Dimming:

UGR:

SDCM:

Luminous efficacy:

luminaire Lifetime:

Material:

Working Temperature (°C):

Transformer availability:

On/Off, 1-10V, DALI, TRIAC

≤15

≤3

78lm/W

50000h (L80B50, T α25° C)

Aluminium

-20° C ~ +45° C

LED DC 36V 120mA

