




Ron

Adjustable trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  L70*W70 mm
-  0°~15°
-  0°~355°
-  Matte White (MW)
-  Matte Black (MB)
-  Matte Silver (MS)
-  Matte Gold (MG)



Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 6W	 15°	02.7501.MW	02.7502.MW	02.7503.MW	02.7504.MW	02.7533.MW
		02.7501.MB	02.7502.MB	02.7503.MB	02.7504.MB	02.7533.MB
		02.7501.MS	02.7502.MS	02.7503.MS	02.7504.MS	02.7533.MS
		02.7501.MG	02.7502.MG	02.7503.MC	02.7504.MG	02.7533.MG
	 24°	02.7505.MW	02.7506.MW	02.7507.MW	02.7508.MW	02.7534.MW
		02.7505.MB	02.7506.MB	02.7507.MB	02.7508.MB	02.7534.MB
		02.7505.MS	02.7506.MS	02.7507.MS	02.7508.MS	02.7534.MS
		02.7505.MG	02.7506.MG	02.7507.MG	02.7508.MG	02.7534.MG
	 36°	02.7509.MW	02.7510.MW	02.7511.MW	02.7512.MW	02.7535.MW
		02.7509.MB	02.7510.MB	02.7511.MB	02.7512.MB	02.7535.MB
		02.7509.MS	02.7510.MS	02.7511.MS	02.7512.MS	02.7535.MS
		02.7509.MG	02.7510.MG	02.7511.MG	02.7512.MG	02.7535.MG
	 50°	02.7513.MW	02.7514.MW	02.7515.MW	02.7516.MW	02.7536.MW
		02.7513.MB	02.7514.MB	02.7515.MB	02.7516.MB	02.7536.MB
		02.7513.MS	02.7514.MS	02.7515.MS	02.7516.MS	02.7536.MS
		02.7513.MG	02.7514.MG	02.7515.MG	02.7516.MG	02.7536.MG

Dimming: On/Off, 1-10V, DALI, TRIAC
 UGR: ≤15
 SDCM: ≤3
 Luminous efficacy: 78lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 150mA

