


Ron

Adjustable trimless Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 60 mm
-  0°~15°
-  0°~355°
-  Matte White (MW)
-  Matte Black (MB)
-  Matte Silver (MS)
-  Matte Gold (MG)



Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 10W	 15°	11.6017.MW	11.6018.MW	11.6019.MW	11.6020.MW	11.6037.MW
		11.6017.MB	11.6018.MB	11.6019.MB	11.6020.MB	11.6037.MB
		11.6017.MS	11.6018.MS	11.6019.MS	11.6020.MS	11.6037.MS
		11.6017.MG	11.6018.MG	11.6019.MC	11.6020.MG	11.6037.MG
	 24°	11.6021.MW	11.6022.MW	11.6023.MW	11.6024.MW	11.6038.MW
		11.6021.MB	11.6022.MB	11.6023.MB	11.6024.MB	11.6038.MB
		11.6021.MS	11.6022.MS	11.6023.MS	11.6024.MS	11.6038.MS
		11.6021.MG	11.6022.MG	11.6023.MG	11.6024.MG	11.6038.MG
	 36°	11.6025.MW	11.6026.MW	11.6027.MW	11.6028.MW	11.6039.MW
		11.6025.MB	11.6026.MB	11.6027.MB	11.6028.MB	11.6039.MB
		11.6025.MS	11.6026.MS	11.6027.MS	11.6028.MS	11.6039.MS
		11.6025.MG	11.6026.MG	11.6027.MG	11.6028.MG	11.6039.MG
	 50°	11.6029.MW	11.6030.MW	11.6031.MW	11.6032.MW	11.6040.MW
		11.6029.MB	11.6030.MB	11.6031.MB	11.6032.MB	11.6040.MB
		11.6029.MS	11.6030.MS	11.6031.MS	11.6032.MS	11.6040.MS
		11.6029.MG	11.6030.MG	11.6031.MG	11.6032.MG	11.6040.MG

Dimming: On/Off, 1-10V, DALI, TRIAC
 UGR: ≤15
 SDCM: ≤3
 Luminous efficacy: 78lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 250mA

