



Cabin

Adjustable trimless Downlight

-  Ceiling recessed
-  AC 220V~240V
-  95
-  Lens
-  Class II
-  Ø 120 mm
-  0°~30°
-  0°~355°
-  Matte White(MW)
-  Matte Black(MB)
-  Matte Silver(MS)
-  Matte Copper(MC)
-  Matte Gold(MG)



Wattage	Beam Angle	2700K	3000K	3500K	4000K
Max. 13W	 13°	11.7017.MW	11.7018.MW	11.7019.MW	11.7020.MW
		11.7017.MB	11.7018.MB	11.7019.MB	11.7020.MB
		11.7017.MS	11.7018.MS	11.7019.MS	11.7020.MS
		11.7017.MC	11.7018.MC	11.7019.MC	11.7020.MC
		11.7017.MG	11.7018.MG	11.7019.MG	11.7020.MG
	 24°	11.7021.MW	11.7022.MW	11.7023.MW	11.7024.MW
		11.7021.MB	11.7022.MB	11.7023.MB	11.7024.MB
		11.7021.MS	11.7022.MS	11.7023.MS	11.7024.MS
		11.7021.MC	11.7022.MC	11.7023.MC	11.7024.MC
		11.7021.MG	11.7022.MG	11.7023.MG	11.7024.MG
	 38°	11.7025.MW	11.7026.MW	11.7027.MW	11.7028.MW
		11.7025.MB	11.7026.MB	11.7027.MB	11.7028.MB
		11.7025.MS	11.7026.MS	11.7027.MS	11.7028.MS
		11.7025.MC	11.7026.MC	11.7027.MC	11.7028.MC
		11.7025.MG	11.7026.MG	11.7027.MG	11.7028.MG
	 50°	11.7029.MW	11.7030.MW	11.7031.MW	11.7032.MW
		11.7029.MB	11.7030.MB	11.7031.MB	11.7032.MB
		11.7029.MS	11.7030.MS	11.7031.MS	11.7032.MS
		11.7029.MC	11.7030.MC	11.7031.MC	11.7032.MC
		11.7029.MG	11.7030.MG	11.7031.MG	11.7032.MG

Dimming: On/Off, 1-10V, DALI, TRIAC
 UGR: ≤8
 SDCM: ≤3
 Luminous efficacy: 78lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 350mA

