

Designed for signage of architectonic



Especially designed for signage of architectonic spaces such as stairs, pathways, etc. IP65 protection degree guaranteeing correct outdoor / indoor use.

Available with next-generation LED light source, suitable for responding to diverse signalling needs on pathways or stairways. Available in different light shades, through coloured internal diffuser.

Embedded light fixture for indoor use in all its finishes, except stainless steel which is suitable for outdoor use.




B-IO






B-O

-  Wall Luminaires
-  AC 220V~240V
-  Ra 85
-  Lens
-  Class II
-  Ø 46 mm
-  White (WH)
-  Black (BK)



Wattage	Beam Angle	2700K	3000K	4000K
Max. 2W	 72°	05.4601.WH 05.4601.BK	05.4602.WH 05.4602.BK	05.4603.WH 05.4603.BK

Dimming:

UGR:

SDCM:

Luminous efficacy:

luminaire Lifetime:

Material:

Working Temperature (°C):

Transformer availability:

On/Off

≤16

≤3

64lm/W

50000h (L80B10, T a25° C)


Aluminium

-20° C ~ +45° C

AC 220V~240V




Installation Schemes




Connection Tips

SEVERAL FIXTURES CONNECTION TO A SINGLE CONSTANT CURRENT DRIVER



Trimless Mounting



Publication date: December 2022

©Copyright OBT lighting

With thank to all contributors for the realization of this catalogue

Designed by OBT lighting Graphic Design Department

No part of this catalogue may be copied without written authorization of OBT lighting



OBT LIGHTING LIMITED

Unit G1 Capital House 61
Amhurst Road, London,
United Kingdom, E8 1LL
services@obtlighting.cn
Hotline : 400 090 2289

www.obt.ltd



Floor 2, No. 979, Yunhan
Road, Lingang New District,
China (Shanghai) pilot Free
Trade Zone
services@obtlighting.cn
Hotline : 400 090 2289

www.obt.ltd

Office 5, 8/F, Mega Cube,
8 Wang Kwong Road, Kowloon
Bay, Kowloon, Hong Kong
services@obtlighting.cn
Hotline : 400 090 2289

www.obt.ltd

Room 201, building 3, No. 67,
Luoja Nanyue street, Dalong
street, Panyu District,
Guangzhou
services@obtlighting.cn
Hotline : 400 090 2289

www.obt.ltd