


O1

Golf Series

Series




Adjustable Downlight

Round-shaped mounting trim in cast aluminum with springs for trim installation on a ceiling thickness of 1-25mm.

Luminaire body in cast aluminum materials.

Easy relamping via removable front ring with twist-lock action for retrofit version.

The fully retractable lighthead is tiltable with up to 35° and rotatable horizontally 350°.



GOLF SERIES



The unique pull-down mechanism enables it to function as either a downlight, a recessed accent light with great cut-off, or a exposed lamp head able to emulate a surface or track fixture.










Golf

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 70 mm
-  0°~35°
-  0°~355°
-  Matte White (MW)
-  Matte Black (MB)
-  Matte Silver (MS)
-  Matte Copper (MC)
-  Matte Gold (MG)










Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 12.5W	15°	02.7201.MW	02.7202.MW	02.7203.MW	02.7204.MW	02.7233.MW
		02.7201.MB	02.7202.MB	02.7203.MB	02.7204.MB	02.7233.MB
		02.7201.MS	02.7202.MS	02.7203.MS	02.7204.MS	02.7233.MS
		02.7201.MC	02.7202.MC	02.7203.MC	02.7204.MC	02.7233.MC
		02.7201.MG	02.7202.MG	02.7203.MG	02.7204.MG	02.7233.MG
	24°	02.7205.MW	02.7206.MW	02.7207.MW	02.7208.MW	02.7234.MW
		02.7205.MB	02.7206.MB	02.7207.MB	02.7208.MB	02.7234.MB
		02.7205.MS	02.7206.MS	02.7207.MS	02.7208.MS	02.7234.MS
		02.7205.MC	02.7206.MC	02.7207.MC	02.7208.MC	02.7234.MC
		02.7205.MG	02.7206.MG	02.7207.MG	02.7208.MG	02.7234.MG
	36°	02.7209.MW	02.7210.MW	02.7211.MW	02.7212.MW	02.7235.MW
		02.7209.MB	02.7210.MB	02.7211.MB	02.7212.MB	02.7235.MB
		02.7209.MS	02.7210.MS	02.7211.MS	02.7212.MS	02.7235.MS
		02.7209.MC	02.7210.MC	02.7211.MC	02.7212.MC	02.7235.MC
		02.7209.MG	02.7210.MG	02.7211.MG	02.7212.MG	02.7235.MG
	50°	02.7213.MW	02.7214.MW	02.7215.MW	02.7216.MW	02.7236.MW
		02.7213.MB	02.7214.MB	02.7215.MB	02.7216.MB	02.7236.MB
		02.7213.MS	02.7214.MS	02.7215.MS	02.7216.MS	02.7236.MS
		02.7213.MC	02.7214.MC	02.7215.MC	02.7216.MC	02.7236.MC
		02.7213.MG	02.7214.MG	02.7215.MG	02.7216.MG	02.7236.MG


Dimming: On/Off, 1-10V, DALI, TRIAC
 UGR: ≤8
 SDCM: ≤3
 Luminous efficacy: 78lm/W
 luminaire Lifetime: 50000h (L80B10, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 350mA



Golf

Adjustable trimless Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 120 mm
-  0°~35°
-  0°~355°
-  Matte White(MW)
-  Matte Black(MB)
-  Matte Silver(MS)
-  Matte Copper(MC)
-  Matte Gold(MG)




Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 12.5W	13°	11.7217.MW	11.7218.MW	11.7219.MW	11.7220.MW	11.7237.MW
		11.7217.MB	11.7218.MB	11.7219.MB	11.7220.MB	11.7237.MB
		11.7217.MS	11.7218.MS	11.7219.MS	11.7220.MS	11.7237.MS
		11.7217.MC	11.7218.MC	11.7219.MC	11.7220.MC	11.7237.MC
		11.7217.MG	11.7218.MG	11.7219.MG	11.7220.MG	11.7237.MG
	24°	11.7221.MW	11.7222.MW	11.7223.MW	11.7224.MW	11.7238.MW
		11.7221.MB	11.7222.MB	11.7223.MB	11.7224.MB	11.7238.MB
		11.7221.MS	11.7222.MS	11.7223.MS	11.7224.MS	11.7238.MS
		11.7221.MC	11.7222.MC	11.7223.MC	11.7224.MC	11.7238.MC
		11.7221.MG	11.7222.MG	11.7223.MG	11.7224.MG	11.7238.MG
	38°	11.7225.MW	11.7226.MW	11.7227.MW	11.7228.MW	11.7239.MW
		11.7225.MB	11.7226.MB	11.7227.MB	11.7228.MB	11.7239.MB
		11.7225.MS	11.7226.MS	11.7227.MS	11.7228.MS	11.7239.MS
		11.7225.MC	11.7226.MC	11.7227.MC	11.7228.MC	11.7239.MC
		11.7225.MG	11.7226.MG	11.7227.MG	11.7228.MG	11.7239.MG
	50°	11.7229.MW	11.7230.MW	11.7231.MW	11.7232.MW	11.7240.MW
		11.7229.MB	11.7230.MB	11.7231.MB	11.7232.MB	11.7240.MB
		11.7229.MS	11.7230.MS	11.7231.MS	11.7232.MS	11.7240.MS
		11.7229.MC	11.7230.MC	11.7231.MC	11.7232.MC	11.7240.MC
		11.7229.MG	11.7230.MG	11.7231.MG	11.7232.MG	11.7240.MG

Dimming: On/Off, 1-10V, DALI, TRIAC
 UGR: ≤8
 SDCM: ≤3
 Luminous efficacy: 78lm/W
 luminaire Lifetime: 50000h (L80B10, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 350mA




Installation Schemes




Connection Tips

SEVERAL FIXTURES CONNECTION TO A SINGLE CONSTANT CURRENT DRIVER



Trimless Mounting



Publication date: December 2022

©Copyright OBT lighting

With thank to all contributors for the realization of this catalogue

Designed by OBT lighting Graphic Design Department

No part of this catalogue may be copied without written authorization of OBT lighting



OBT LIGHTING LIMITED

Unit G1 Capital House 61
Amhurst Road, London,
United Kingdom, E8 1LL
services@obtlighting.cn
Hotline : 400 090 2289

www.obt.ltd



Floor 2, No. 979, Yunhan
Road, Lingang New District,
China (Shanghai) pilot Free
Trade Zone
services@obtlighting.cn
Hotline : 400 090 2289

www.obt.ltd

Office 5, 8/F, Mega Cube,
8 Wang Kwong Road, Kowloon
Bay, Kowloon, Hong Kong
services@obtlighting.cn
Hotline : 400 090 2289

www.obt.ltd

Room 201, building 3, No. 67,
Luoja Nanyue street, Dalong
street, Panyu District,
Guangzhou
services@obtlighting.cn
Hotline : 400 090 2289

www.obt.ltd